

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number  
**WO 2004/031566 A1**

(51) International Patent Classification<sup>7</sup>: **F02M 27/04**,  
F02B 51/04

(21) International Application Number:  
PCT/IT2003/000576

(22) International Filing Date:  
26 September 2003 (26.09.2003)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:  
RM2002A000495 2 October 2002 (02.10.2002) IT

(71) Applicant and  
(72) Inventor: TURL, Carlo [IT/IT]; Via Graziano, 57, I-00167  
Roma (IT).

(74) Agents: IANNONE, Carlo, Luigi et al.; Ing. Barzano  
& Zanardo Roma S.p.A., Via Piemonte, 26, I-00187 Rome  
(IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,  
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,  
MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT,  
RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR,  
TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

- with international search report
- before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: MAGNETIC CONDITIONING APPARATUS FOR DIESEL ENGINE FUEL



(57) **Abstract:** The invention relates to a magnetic conditioning device for diesel engine fuel comprising a housing element, placed along the fuel feeding line, having a fuel inlet and a fuel outlet, and providing a septum in correspondence of the inlet to deviate the inlet fuel, and an obliged path for the fuel, being provided at least two opposed magnetic elements. Along said obliged path, inducing a magnetic field on the flowing fuel.